

Appln No. 09/403,472

Amdt date August 8, 2003

Reply to Office action of May 8, 2003

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended) An optical resonator comprising reflector elements and at least one static discontinuous phase element disposed between said reflector elements, said at least one discontinuous phase element having at least one sharp discontinuity adapted to introduce a discontinuous phase change in at least one undesired mode propagating in said resonator, and wherein said at least one discontinuous phase element is aligned such that said at least one sharp discontinuity falls in a region of low intensity of a desired mode propagating in said resonator. pp. 12, 14

2. (Original) An optical resonator according to claim 1, and whose said reflector elements are at least one full reflector and an output coupler.

3. (Previously amended) An optical resonator according to claim 1, and being a passive optical resonator.

4. (Original) An optical resonator according to either of the preceding claims 1 and 2, and being an active optical resonator.

Appln No. 09/403,472

Amdt date August 8, 2003

Reply to Office action of May 8, 2003

5. (Previously amended) An optical resonator according to claim 1, and being the resonator of a laser.

6. (Previously amended) An optical resonator according to claim 1, and being the resonator of a ring laser.

7. (Previously amended) An optical resonator according to claim 1, and being a stable resonator.

8. (Previously amended) An optical resonator according to claim 1, and being an unstable resonator.

DI
Contd 9. (Previously amended) An optical resonator according to claim 1, and wherein said at least one discontinuous phase element is embodied in a reflector of said optical resonator.

10. (Previously amended) An optical resonator according to claim 1, and wherein said at least one discontinuous phase element is embodied in an output coupler of said optical resonator.

11. (Previously amended) An optical resonator according to claim 1, and wherein said at least one discontinuous phase element is positioned adjacent to an optical element of said optical resonator.

Appln No. 09/403,472

Amdt date August 8, 2003

Reply to Office action of May 8, 2003

12. (Previously amended) An optical resonator according to claim 1, and wherein said at least one discontinuous phase element is placed inside said optical resonator at a defined point which is imaged onto itself from an optical element within the resonator.

*D1
contd*
13. (Previously amended) An optical resonator according to claim 1, and wherein said at least one discontinuous phase element is positioned adjacent to a flat output coupler of said optical resonator, and the full reflector of said resonator is curved.

14. (Previously amended) An optical resonator according to claim 1, and wherein said at least one discontinuous phase element also provides at least one of angular, linear and radial phase change.

15. (Previously amended) An optical resonator according to claim 1, and also comprising an external discontinuous phase element having at least one sharp discontinuity, operative in addition to said at least one discontinuous phase element disposed between said reflector elements, in order to improve an output beam from said optical resonator.

16. (Cancelled)

Appln No. 09/403,472

Amdt date August 8, 2003

Reply to Office action of May 8, 2003

17. (Previously added) An optical resonator according to claim 1, and wherein said at least one discontinuous phase element changes the phase of predetermined parts of a desired mode of said resonator, such that generally all parts of the emerging field distribution of said mode are in phase.

18. (Previously added) An optical resonator according to claim 1, and wherein said at least one discontinuous phase element is disposed such that said at least one sharp discontinuity falls in a region of high intensity of at least one undesirable mode of said resonator.

DI
Contd
19. (Previously added) An optical resonator according to claim 18, and wherein said at least one discontinuous phase element causes the divergence of said at least one undesirable mode in said resonator to be greater than that of a desired mode, such that propagation of said undesirable mode is decreased.

20. (Currently amended) A method of improving the output beam quality of a laser, comprising the steps of:

providing a laser resonator having reflector elements and a gain medium; ~~and~~

disposing at least one discontinuous phase element between said reflector elements, said at least one discontinuous phase element having at least one sharp discontinuity adapted to introduce a discontinuous phase change in at least one undesired mode propagating in said laser resonator; and

Appln No. 09/403,472
Amdt date August 8, 2003
Reply to Office action of May 8, 2003

aligning said at least one discontinuous phase element such that said at least one sharp discontinuity falls in a region of low intensity of a desired mode propagating in said laser resonator.

21. (Currently amended) The method of claim 20, and also comprising the step of selecting said at least one discontinuous phase element such that said laser resonator oscillates in at least one mode having a higher order [mode] than the Gaussian mode ~~[that obtained without said at least one discontinuous phase element, thereby resulting in an increase of power of]~~ such that said output beam of said laser has a higher power than that of the Gaussian mode.

D'
Cont'd

22. (Currently amended) The method of claim 21, and wherein said at least one higher order mode is a single mode.

23. (Currently amended) The method of claim 21, and wherein said laser is an unstable resonator laser~~[, such that the generation of a higher intensity center spot in said output beam is reduced]~~.

24. (Previously added) The method of claim 21, and wherein said laser is a solid state laser.

25. (Currently amended) The method of claim 24, and wherein said higher ~~[increase of]~~ power of said output beam does not limit the dynamic range of said laser.

Appln No. 09/403,472

Amdt date August 8, 2003

R ply to Office action of May 8, 2003

26. (Previously added) The method of claim 24, and wherein said at least one discontinuous phase element is selected such that compensation is provided for birefringence distortion introduced by said gain medium.

27. (Previously added) The method of claim 24, and wherein said at least one discontinuous phase element is selected such that thermal lensing in said gain medium is reduced.

28. (Previously added) The method of claim 24, and wherein said laser resonator also comprises a non-linear crystal, and wherein said at least one discontinuous phase element is selected and disposed such that the intensity of said resonator mode in said non-linear crystal is generally higher than its intensity in said gain medium.

29. (New) An optical resonator according to claim 11, and wherein said at least one discontinuous phase element is disposed adjacent to said output coupler of said optical resonator, such that essentially all parts of an output beam of a desired mode of said resonator are in phase.
